

FORM PTO-1390 (Modified)  
(REV 11-2000)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

294-117 PCT/US

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

10/031850

INTERNATIONAL APPLICATION NO  
PCT/NL00/00518INTERNATIONAL FILING DATE  
July 21, 2000PRIORITY DATE CLAIMED  
July 23, 1999

TITLE OF INVENTION

DEVICE FOR STORAGE AND CONVEYANCE OF BULKY HOLDERS

APPLICANT(S) FOR DO/EO/US

Hoogland, Hendrik Antonius

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below.
4. ☒ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
  - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☒ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
  - a. ☐ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☒ A copy of the International Search Report (PCT/ISA/210).

## Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
20. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
21. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
22. ☒ Certificate of Mailing by Express Mail
23. ☒ Other items or information:

Copy of the international patent application as published under International Publication Number WO 01/07345 A1

## EXPRESS MAIL CERTIFICATE

Date: 1-23-02 Label No. EL709115945 US  
 I hereby certify that the date indicated above, I deposited this paper or fee with the U.S. Postal Service and that it was addressed for delivery to the Commissioner for Patents, Washington, DC 20231 by "EXPRESS MAIL Post Office to Addressee" Service.

Joan Newbert  
(Print Name)Joan Newbert  
(Signature)

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.53) <b>10/031850</b>	INTERNATIONAL APPLICATION NO. <b>PCT/NL00/00518</b>	ATTORNEY'S DOCKET NUMBER <b>294-117 PCT/US</b>
--	--	---

24. The following fees are submitted:.

**BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5) ) :**

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... **\$1040.00**
- ☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... **\$890.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... **\$740.00**
- ☐ International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... **\$710.00**
- ☐ International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... **\$100.00**

**ENTER APPROPRIATE BASIC FEE AMOUNT =****\$890.00**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

**\$0.00**

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	16 - 20 =	0	x \$18.00
Independent claims	1 - 3 =	0	x \$84.00

**\$0.00****\$0.00**Multiple Dependent Claims (check if applicable). ☐**\$0.00****TOTAL OF ABOVE CALCULATIONS =****\$890.00**

☐ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.

**\$0.00****SUBTOTAL =****\$890.00**

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

**\$0.00****TOTAL NATIONAL FEE =****\$890.00**

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐

**\$0.00****TOTAL FEES ENCLOSED =****\$890.00****Amount to be:****refunded**

\$

**charged**

\$

- a. ☒ A check in the amount of **\$890.00** to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees. A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. **08-2461**. A duplicate copy of this sheet is enclosed.
- d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.

**NOTE:** Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Ronald J. Baron, Esq.  
Hoffmann & Baron, LLP  
6900 Jericho Turnpike  
Syosset, New York 11791  
United States of America

Telephone: 516-822-3550  
Facsimile: 516-822-3582

SIGNATURE

Ronald J. Baron

NAME

29,281

REGISTRATION NUMBER

January 23, 2002

DATE

10/031850

531 Rec'd PCT

23 JAN 2002

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s)	Hoogland, Hendrik Antonius	Examiner:	Unassigned
Serial No:	Unassigned	Group Art Unit:	Unassigned
Confirmation No:	Unassigned	Docket:	294-117 PCT/US
Filed:	Herewith	Dated:	January 23, 2002
For:	DEVICE FOR STORAGE AND CONVEYANCE OF BULKY HOLDERS		

Commissioner for Patents  
Washington, DC 20231

*Express Mail Certificate:*

Date: 1-23-02 Label No: EL709115945 JS

*I hereby certify that on the date indicated above, I  
deposited this paper or fee with the United States  
Postal Service and that it was addressed for delivery  
to the Assistant Commissioner for Patents,  
Washington, D.C. 20231 on January 23, 2002*

Signature: Jon M. Newbert

PRELIMINARY AMENDMENT

Sir:

In order to place the present application in condition for examination on the merits,  
e.g., to eliminate the multiple dependencies found claims 4, 6-16, Applicant submits the  
following amendment for entry in the above-identified application.

IN THE SPECIFICATION:

On page 1, delete the title and insert therefor the following:

DEVICE FOR STORAGE AND CONVEYANCE OF BULKY HOLDERS

10031850-0584E001

Applicant: Hoogland, Hendrik Antonius  
Serial No.: Unassigned  
Our Docket: 294-117 PCT/US  
Page 2

On page 1, before line 1, after the title, please insert the following:

This application is the U.S. National Phase of International Application  
Number PCT/NL00/00518, filed July 21, 2000, which is incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

On page 2 between lines 31 and 32 insert the following:

**SUMMARY OF THE INVENTION**

On page 6, between lines 26 and 27 insert the following:

**BRIEF DESCRIPTION OF THE DRAWINGS**

And between lines 35 and 36 insert the following:

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

0051850-0001

**IN THE CLAIMS:**

Please amend Claims 4, and 6 through 16 to read as follows:

4. (Amended) Device according to claim 1, in which the transverse tracks are formed by rotatable discs (40) which are disposed one after the other in rows and are rotatable about a horizontal shaft (42) and in the longitudinal direction of a transverse track.

6. (Amended) Device according to claim 4, in which the underside of a carrier (14) between the rows of wheels (16) is provided with guides (44) for accommodating and guiding the rotatable discs (40).

7. (Amended) Device according to claim 1, in which the carriers (14) are provided with spacers (46).

8. (Amended) Device according to claim 1, in which the longitudinal paths (4, 6) are provided with blocking means (48) for retaining a carrier (14).

9. (Amended) Device according to claim 1, provided with a supply point (12) and removal point (10) for feeding in and removing containers (C) respectively.

10. (Amended) Device according to claim 1, in which the supply point (12) and removal point (10) are situated at the same end of the longitudinal paths (4, 6) of the device.

11. (Amended) Device according to claim 1, in which the supply point (12) and removal point (10) are situated at the end of the longitudinal paths (4, 6) where the height difference between them is minimal.

12. (Amended) Device according to claim 1, in which a detection system for detecting a unique code is present, which code ( $C_n$ ) is placed on a holder (C).

13. (Amended) Device according to claim 1, in which each conveyance circuit (2) comprises two parallel longitudinal paths (4, 6), and each tier (32) comprises several conveyance circuits (2) disposed next to each other.

14. (Amended) Device according to claim 1, provided with a further conveyor, which moves along each supply and removal point (12, 10) of a conveyance circuit (2), and over which lifting means for conveying holders are disposed in a movable manner.


16. (Amended) Container terminal provided with a device according to claim 1.

**REMARKS**

In order to place the present application in condition for examination in the U.S. Patent Office, e.g., by eliminating multiple dependencies, Applicant has amended certain claims to be singly dependent from previous claims. No new subject matter has been introduced as a result of this Amendment. As a result of the present Amendment, Claims 1-16 remain in the application for purpose of prosecution.

As a result of this Amendment no additional fees should be assessed as a result of filing multiple dependent claims. Therefore, since new matter has not been introduced as a result of this Amendment, entry hereof and examination and favorable consideration are respectfully requested. Any questions regarding this matter should be directed to the undersigned.

Respectfully submitted,

A handwritten signature in black ink, appearing to read 'Ronald J. Baron', is written over a horizontal line.

Ronald J. Baron  
Registration No: 29,281  
Attorney for Applicant

HOFFMANN & BARON, LLP  
6900 Jericho Turnpike  
Syosset, New York 11791  
(516) 822-3550  
RJB/jmn



10/031850

Applicant: Hoogland, Hendrik Antonius  
Serial No.: Unassigned  
Our Docket: 294-117 PCT/US  
Page 7

531 Rec'd PCT.

23 JAN 2002

**VERSION OF AMENDMENT WITH MARKS**  
**TO SHOW CHANGES MADE**

**IN THE SPECIFICATION:**

On page 1, delete the title and insert therefor the following:

**DEVICE FOR STORAGE AND CONVEYANCE OF BULKY HOLDERS**

On page 1, before line 1, after the title, please insert the following:

This application is the U.S. National Phase of International Application  
Number PCT/NL00/00518, filed July 21, 2000, which is incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

On page 2 between lines 31 and 32 insert the following:

**SUMMARY OF THE INVENTION**

2000051850

On page 6, between lines 26 and 27 insert the following:

**BRIEF DESCRIPTION OF THE DRAWINGS**

And between lines 35 and 36 insert the following:

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

**IN THE CLAIMS:**

Please amend Claims 4, and 6 through 16 to read as follows:

4. (Amended) Device according to claim 1 [one of the preceding claims], in which the transverse tracks are formed by rotatable discs (40) which are disposed one after the other in rows and are rotatable about a horizontal shaft (42) and in the longitudinal direction of a transverse track.

6. (Amended) Device according to claim 4 [or 5], in which the underside of a carrier (14) between the rows of wheels (16) is provided with guides (44) for accommodating and guiding the rotatable discs (40).

7. (Amended) Device according to claim 1 [one of the preceding claims], in which the carriers (14) are provided with spacers (46).

8. (Amended) Device according to claim 1 [one of the preceding claims], in which the longitudinal paths (4, 6) are provided with blocking means (48) for retaining a carrier (14).

9. (Amended) Device according to claim 1 [one of the preceding claims], provided with a supply point (12) and removal point (10) for feeding in and removing containers (C) respectively.

10. (Amended) Device according to claim 1 [one of the preceding claims], in which the supply point (12) and removal point (10) are situated at the same end of the longitudinal paths (4, 6) of the device.

11. (Amended) Device according to claim 1 [one of the preceding claims], in which the supply point (12) and removal point (10) are situated at the end of the longitudinal paths (4, 6) where the height difference between them is minimal.

12. (Amended) Device according to claim 1 [one of the preceding claims], in which a detection system for detecting a unique code is present, which code ( $C_n$ ) is placed on a holder (C).

13. (Amended) Device according to claim 1 [one of the preceding claims], in which each conveyance circuit (2) comprises two parallel longitudinal paths (4, 6), and each tier (32) comprises several conveyance circuits (2) disposed next to each other.

14. (Amended) Device according to claim 1 [one of the preceding claims], provided with a further conveyor, which moves along each supply and removal point (12, 10) of a conveyance circuit (2), and over which lifting means for conveying holders are disposed in a movable manner.

15. (Amended) Device according to claim 1 [one of the preceding claims], in which the second predetermined number (M) of carriers (14) movable along the longitudinal paths and transverse tracks is equal to twice the first predetermined number (N) of holder positions of a longitudinal path (4, 6) adjoining each other, minus one.

16. (Amended) Container terminal provided with a device according to claim 1 [one of the preceding claims].

Device for storage and conveyance of bulky holders

The present invention relates to a device for storage and conveyance of bulky holders, in particular containers.

Container terminals are generally known and are used for the  
5 temporary storage and subsequent distribution of containers, which  
are brought into a seaport in large numbers in, for example,  
container ships, and are then transported further by rail in goods  
trains, by road in lorries or on waterways in smaller vessels. In  
order to permit temporary storage of the large quantity of  
10 containers, said containers are stacked on top of one another in  
rows spaced apart in a storage yard, generally with the aid of  
mobile gantry cranes operated by crane drivers. The free space  
between the rows is necessary for the tracks along which the mobile  
cranes can move. When a particular container from such a stack has  
15 to be transported further, the containers stacked on top of this  
particular container first have to be moved to a free position  
before the particular container can be removed from the stack and  
delivered for further distribution to a generally centrally  
situated discharge point. Such movements take a relatively large  
20 amount of time. Moreover, it is found in practice that a container,  
once stored, is often moved about ten times before it is removed  
from the storage site. However, each movement usually has to be  
paid for, which incurs additional costs. Furthermore, the space is  
being used inefficiently, since aisles are needed between the rows  
25 for the gantry cranes.

The same problem occurs in distribution centres, where pallets  
or other holders filled with goods are stored temporarily on racks  
comprising several levels. Here again, aisles have to be present  
between the racks and at their ends, for forklift trucks or the  
30 like which supply and remove the pallets. A large amount of floor  
space is therefore needed. However, the pallets are not stacked  
directly on top of one another and can therefore be removed  
individually from the racks.

A solution known from the trade is described in, for example,  
35 WO 94/06708, which discloses a storage system for bulky holders, in  
particular containers used in aircraft. This system consists of a

number of storage levels, each consisting of mutually parallel, individually operable endless horizontal longitudinal conveyors with storage bays for the stored holders. On each level, provision is made for (endless) transverse conveyors at least at the two ends of the horizontal longitudinal conveyors. Aisles between the horizontal longitudinal conveyors are therefore not required.

A disadvantage of such a system is that separate drives, such as chain drives, are needed for each conveyor, as are separate intermediate parts, for example roller conveyors, for transferring a container from a longitudinal conveyor to a transverse conveyor.

EP-A-0 145 871 also discloses a device for the storage and conveyance of containers, in which a so-called "Doppelfahrwagen" (double carriage), which can travel along a network of rails provided with crossover points, is used. Such a carriage is provided with a first travelling mechanism comprising several sets of first travelling wheels, for movement in a first direction, and with a second travelling mechanism comprising several sets of second travelling wheels, for movement in another direction, generally transversely to the first direction, the travelling mechanisms being adjustable in height relative to each other, so that when the first travelling mechanism is resting on the rails and the second has been retracted the carriage with load can move in the first direction, and vice versa. The change in direction of movement can be made at the crossover points. This means that turntables, bends and the like in the network are not needed. These carriages known from EP-A 0 145 871 are provided with a lifting table, so that no additional aids, such as cranes and the like, are needed for loading and unloading.

Disadvantages of this known system are that drives are needed for moving the carriages, and that each carriage has to be provided with a double travelling mechanism.

The object of the present invention is to reduce the abovementioned problems, in particular to limit the number of drives and in doing so to keep the construction relatively simple, while the possibility of automation and also efficient utilization of space are retained.

To that end, the present invention provides a device for storage and conveyance of bulky holders, comprising at least one tier, each tier comprising at least one conveyance circuit for the holders, and each conveyance circuit comprising at least two

- 3 -

longitudinal paths disposed substantially parallel to each other, for conveyance of the holders in the direction of the longitudinal paths, which longitudinal paths each define a first predetermined number (N) of adjoining holder positions for the holders, while two adjacent longitudinal paths of a conveyance circuit slope from the same end in opposite directions, and also comprising transverse tracks situated at the opposite ends of the longitudinal paths and movable at least in the vertical direction, for conveyance of the holders in the direction of the transverse tracks, which transverse tracks can transfer the holders to and from the longitudinal paths, and also comprising a second predetermined maximum number ( $M \leq 2 \cdot N - 1$ ) of carriers which are movable along the longitudinal paths and transverse tracks and are designed to take one or more holders, lifting means being provided for moving the transverse tracks in the vertical direction.

The device according to the invention comprises at least one tier, and preferably several tiers, situated above one another on a suitable frame of, for example, concrete columns with cross beams. Holders such as pallets or containers can be stored and conveyed on each tier. For this purpose, a conveyance circuit is provided on each tier, along which the stored holders can be conveyed one behind the other with the aid of the movable carriers, substantially under the influence of gravity. Each conveyance circuit comprises at least two, and preferably also two, longitudinal paths which run parallel to each other, but slope from one end in opposite directions. Transverse tracks which are movable in the vertical direction form connecting routes for the holders at the ends of the longitudinal paths, so that the whole system forms a closed circuit. The device is further provided with carriers which are movable along the longitudinal paths and transverse tracks. The length of a longitudinal path is such that a predetermined number (N) of carriers with holders fit on it. The total number of carriers (M) is then less than or equal to  $2 \cdot N - 1$ , so that a free position in the conveyance circuit is present in each case. This makes movement possible. Since the longitudinal paths are disposed in a sloping manner, an angle of inclination of  $0.2^\circ$  being sufficient for 8 standard 40-foot containers disposed crosswise, the containers disposed upon the carriers, as a result of gravity, have the tendency to move by themselves towards the lowest point, so that additional drives are not needed. In order to

transfer a carrier situated at one end of a longitudinal path to an adjoining longitudinal path, the transverse tracks forming the transverse connection at the ends of the longitudinal paths are movable in the vertical direction, so that the carrier is temporarily lifted up from a longitudinal path and is moved along the transverse tracks, preferably again under the influence of gravity, if the transverse tracks are provided with a suitable angle of inclination. Thereafter, the carrier is allowed to rest upon the adjoining longitudinal path again, so that further movement along the latter is possible. The lifting means, for example hydraulic piston/cylinder assemblies, are provided for this vertical movement, which is accompanied by a slight tilt if necessary.

The operation of the device is relatively simple. A tier with  $2 \cdot N$  positions for holders and  $2 \cdot N - 1$  carriers is filled with holders, in principle one on each carrier. However, the carriers may be arranged in such a way that several holders with smaller dimensions fit on them. When a certain holder has to be transported further from there, the circuit in question is put into operation, the carriers being allowed to circulate until the holder in question is situated at a discharge point of a longitudinal path, where said holder can be removed from the circuit. The holder is lifted off a carrier using suitable means, for example a forklift truck. A new holder can be placed on the empty carrier and stored in this way.

The carriers are advantageously mobile along the longitudinal paths, and to that end comprise rows of wheels which are spaced apart and are rotatable in the longitudinal direction of the longitudinal paths. Although in principle a limited number of wheels (e.g. 4) will suffice, it is preferable to use a large number of relatively small wheels, so that if one wheel becomes defective, the entire system does not come to a standstill. The wheels may be disposed on a common axle or otherwise.

The end sections of the longitudinal paths preferably comprise guides for the wheels, which guides are spaced apart, for example guides with an L-profile or an inverted T-profile, such as rails, or guides in the form of a channel (inverted U-profile), the space between the guides being at least partially open, for a reason to be described in further detail.

The transverse tracks are advantageously composed of rotatable



- 5 -

discs or wheels which are disposed one after the other in rows and are rotatable about a horizontal shaft and in the longitudinal direction of the transverse tracks or wheels, along which the carriers are movable in the longitudinal direction of the transverse tracks. According to a further embodiment, each disc is mounted on the head of a piston/cylinder assembly, which piston/cylinder assemblies form the lifting means for the transverse tracks and are movable from the bottom vertically upwards into the open spaces between the guides of the end positions of the longitudinal paths. It will be understood that the stroke of the piston/cylinder assemblies disposed at the end of the longitudinal paths, where the latter have the greatest mutual height difference, must be greater than that of the piston/cylinder assemblies at the other end. In order to ensure that a carrier can roll correctly over the discs, guides such as inverted U-profiles are advantageously provided between the rows of wheels on the underside of the carrier, for accommodating and guiding the rotatable discs, which guides extend in the transverse direction of the carrier.

Since the carriers are positioned in a virtually horizontal position by means of the transverse tracks, before the carriers can be transferred from one longitudinal path by way of the transverse tracks to an adjoining longitudinal path, blocking means are advantageously provided in the longitudinal paths, in particular for the carriers in the penultimate positions, so that sufficient distance is present between the holders on the last (lowest) carrier and penultimate carrier to allow the horizontal positioning. Blocks which can be lowered in the surface are an example of such blocking means, which are actuated, for example, when sensors detect the presence of a carrier in the last position. Spacers between the carriers can produce the same effect, but lead to an overall lengthening and widening of the conveyance circuit with the same number of carriers.

The device according to the invention advantageously has for each conveyance circuit a supply point for supplying new holders when an empty carrier is present, and a removal point for removing a stored holder. These points are advantageously situated at the same ends of the longitudinal paths, in other words, at the head end, so that the holders can be supplied and removed there using one and the same aid, such as a forklift truck. The supply point

and removal point of a conveyance circuit are advantageously situated at the ends of the longitudinal paths, where the height difference is minimal.

For an automated device according to the invention, detection  
5 points are advantageously present both at the supply point and at the removal point, for detection and identification of the holders. The detection system in question, for example a camera identification system, is dependent upon the type of coding present on the holders. When a new holder is fed into a conveyance circuit,  
10 the data of the holder are detected and stored in a computer, together with the data of the conveyance circuit concerned. The computer forms part of the control system of the device. When a particular holder has to be removed from storage, the circuit concerned is put into operation, until through circulation the presence of this particular holder is detected at the removal point.

Several adjoining conveyance circuits, each consisting of two longitudinal paths, are advantageously present for each tier.

The device can also be provided with a further conveyor, which  
20 moves along each supply and removal point of a conveyance circuit, and on which lifting means for conveying, supplying and removing the holders are disposed in a movable manner.

The invention also relates to a container terminal provided with a device according to the invention.

25 The device according to the invention is explained below with reference to the appended drawing, in which:

Figs. 1a-1e show diagrammatically in a view from above the circulation of holders in a conveyance circuit according to the invention;

30 Fig. 2 shows a diagrammatic side view of the conveyance circuit according to Fig. 1a;

Fig. 3 shows a side view of a part of an end section of a longitudinal path of the conveyance circuit; and

Fig. 4 shows a side view of a part of a transverse track of  
35 the conveyance circuit.

Figs. 1a to 1e show diagrammatically in top view the circulation route of containers  $C_m$ , E representing an empty position. The direction of circulation is indicated by arrows. A conveyance circuit is indicated by reference numeral 2, said  
40 conveyance circuit consisting of a longitudinal path 4 and a

- 7 -

longitudinal path 6, which is disposed parallel to and adjoining longitudinal path 4. See Fig. 2, which is a diagrammatic side view of the situation shown in Fig. 1a. The longitudinal paths 4 and 6 have opposite angles of inclination of approximately  $0.2^\circ$ , which is greatly exaggerated in this figure for the sake of clarity. For the sake of simplicity, transverse tracks are not shown in these Figures 1 and 2. In the situation shown, each longitudinal path has eight positions for carriers with containers. The longitudinal path 4 is filled with carriers with containers  $C_1 - C_8$ , while the longitudinal path 6 comprises containers  $C_9 - C_{15}$  and also has an empty position E that corresponds to the top end position of the longitudinal path 6. The carrier with container  $C_1$  can be moved in a manner to be described in greater detail from the longitudinal path 4 to the empty position E of the longitudinal path 6, so that an empty position E arises in the lowest end position of the longitudinal path 4. See Fig. 1b. By their own weight, the carriers with containers  $C_2 - C_8$  subsequently each drop one position, as shown in Fig. 1c, so that the empty position E now arises at the top end of the longitudinal path 4. The carrier with container  $C_9$  can be lifted up on a vertically movable transverse track until it is above the top end of the longitudinal path 4 and can subsequently be moved along the transverse track to the top position of longitudinal path 4. See Fig. 1d. The empty position E, which is now situated at the bottom end of longitudinal path 6, will be filled by the series of containers  $C_{10} - C_{15}$  moving under the influence of gravity, leading to the situation shown in Fig. 1e, from which it can be seen that all containers C have moved up one position. The cycle described above will be repeated during operation of the device according to the invention for the number of times that it takes for a desired container to be situated at a removal point 10, which is preferably the position at the bottom end of the top longitudinal path 4, while a supply point 12 is preferably the position at the top end of the bottom longitudinal path 6.

As shown in Fig. 3, each longitudinal path 4, 6 comprises a bearing structure along which a carrier 14 with container (not shown) can travel. For that purpose, the carrier 14 is provided with rows of wheels 16 which are spaced apart in the direction of travel, and of which only the outermost wheels of each row are visible in side view. The wheels 16 of a certain row can be mounted

- 8 -

on a common horizontal axle 18, or each wheel can be provided with its own axle. The resulting mobile carrier 14 is provided with suitable means for fixing the containers, for example of the type used for fixing on lorries or rail wagons, for example pins 24 which can be recessed in the top surface 22 of the carrier 14, which pins, for the fixing, project into fitted holes of the container. An end section 26 of a longitudinal path 4, 6 comprises guides 28, running parallel, viewed in the direction of travel, the number of which corresponds to the number of wheels 16 in a row. Open spaces 30 are present between the guides 28 in the end section 26. A number of piston/cylinder assemblies 34 are disposed vertically below these open spaces 30 in the guides 28 on the tier floor 32. A rotatable disc 40 is mounted on the head 36 of each piston 38 in such a way that it can rotate about a horizontal shaft 42, the direction of rotation of a rotatable disc 40 extending transversely to the longitudinal paths 4, 6, i.e. in the direction of movement of the transverse tracks. These rotatable discs 40 form the transverse tracks along which a carrier 14 can be moved from a longitudinal path 4 to an adjoining longitudinal path 6, and vice versa. On the underside of the carrier 14, inverted U-profiles 44 are fixed between the rows of wheels 16, which profiles extend across the entire width of a carrier 14 and ensure correct movement of the carrier 14 along the rotatable discs 40. In order to make the transverse movement possible when a carrier 14 is situated in the bottom end position of a longitudinal path, the pistons 38 are extended until the carrier 14 is no longer resting upon the guides 28, but is resting with the U-profiles 44 upon the rotatable discs 40 and is situated substantially in a horizontal position. A sloping track can be formed by subsequently operating in a controlled manner the rows of piston/cylinder assemblies disposed in the transverse direction of the transverse tracks, along which sloping track the carrier 14 will move under the influence of gravity until said carrier is situated above an end section of the adjoining longitudinal path 6, after which the carrier 14 is again taken substantially into a horizontal position by correct operation of the piston/cylinder assemblies and is subsequently placed in a position corresponding to the angle of inclination of the longitudinal path 6 and then set on the guides 28 by retraction of the pistons 38.

In order to prevent following carriers with containers from

- 9 -

resting against the carrier 14 with container in the end position and making it impossible for the latter to be moved into a horizontal position, spacers 46 are provided at the ends of the carriers 14, and blocking means, for example blocks 48 which can be  
5 recessed in the guides 28 and block further movement of the next carrier, can also be provided. When the last position is free, the blocking means 48 are put out of action, so that the series of carriers can move up one position in the longitudinal path.

Although the above description focuses on a storage device for 10 containers, it will be understood that the device according to the invention can also be used for other holders, for example pallets.

- 10 -

CLAIMS

1. Device for storage and conveyance of bulky holders (C), comprising at least one tier (32), each tier comprising at least one conveyance circuit (2) for the holders (C), and each conveyance circuit (2) comprising at least two longitudinal paths (4, 6) disposed substantially parallel to each other, for conveyance of the holders (C) in the direction of the longitudinal paths (4, 6), which longitudinal paths (4, 6) each define a first predetermined number (N) of adjoining holder positions for the holders (C), while two adjacent longitudinal paths (4, 6) of a conveyance circuit (2) slope from the same end in opposite directions, and also comprising transverse tracks situated at the opposite ends of the longitudinal paths and movable at least in the vertical direction, for conveyance of the holders (C) in the direction of the transverse tracks, which transverse tracks can transfer the holders (C) to and from the longitudinal paths (4, 6), and also comprising a second predetermined number ( $M \leq 2 \cdot N - 1$ ) of carriers (14) which are movable along the longitudinal paths and transverse tracks and are designed to take one or more holders (C), lifting means (34) being provided for moving the transverse tracks in the vertical direction.

2. Device according to claim 1, in which the carriers (14) are provided with rows of wheels (16) which are spaced apart and are rotatable in the longitudinal direction of the longitudinal paths (4, 6).

3. Device according to claim 2, in which at least end sections of the longitudinal paths (4, 6) comprise guides (28) for guiding the wheels (16) of the carrier (14), open spaces (30) being present between the guides (28).

4. Device according to one of the preceding claims, in which the transverse tracks are formed by rotatable discs (40) which are disposed one after the other in rows and are rotatable about a horizontal shaft (42) and in the longitudinal direction of a transverse track.

5. Device according to claim 4, in which a rotatable disc (40) is fixed on the head (36) of a piston/cylinder assembly (34).

6. Device according to claim 4 or 5, in which the underside of a carrier (14) between the rows of wheels (16) is provided with guides (44) for accommodating and guiding the rotatable discs (40).

- 11 -

7. Device according to one of the preceding claims, in which the carriers (14) are provided with spacers (46).

8. Device according to one of the preceding claims, in which the longitudinal paths (4, 6) are provided with blocking means (48) for

5 retaining a carrier (14).

9. Device according to one of the preceding claims, provided with a supply point (12) and removal point (10) for feeding in and removing containers (C) respectively.

10. Device according to one of the preceding claims, in which the supply point (12) and removal point (10) are situated at the same end of the longitudinal paths (4, 6) of the device.

11. Device according to one of the preceding claims, in which the supply point (12) and removal point (10) are situated at the end of the longitudinal paths (4, 6) where the height difference between them is minimal.

12. Device according to one of the preceding claims, in which a detection system for detecting a unique code is present, which code (C<sub>n</sub>) is placed on a holder (C).

13. Device according to one of the preceding claims, in which each conveyance circuit (2) comprises two parallel longitudinal paths (4, 6), and each tier (32) comprises several conveyance circuits (2) disposed next to each other.

14. Device according to one of the preceding claims, provided with a further conveyor, which moves along each supply and removal point (12, 10) of a conveyance circuit (2), and over which lifting means for conveying holders are disposed in a movable manner.

15. Device according to one of the preceding claims, in which the second predetermined number (M) of carriers (14) movable along the longitudinal paths and transverse tracks is equal to twice the first predetermined number (N) of holder positions of a longitudinal path (4, 6) adjoining each other, minus one.

16. Container terminal provided with a device according to one of the preceding claims.





1/5




Fig 1a




Fig 1b

2/5

E	C <sub>8</sub>	C <sub>7</sub>	C <sub>6</sub>	C <sub>5</sub>	C <sub>4</sub>	C <sub>3</sub>	C <sub>2</sub>
C <sub>9</sub>	C <sub>10</sub>	C <sub>11</sub>	C <sub>12</sub>	C <sub>13</sub>	C <sub>14</sub>	C <sub>15</sub>	C <sub>1</sub>

Fig 1c

C <sub>8</sub>	C <sub>7</sub>	C <sub>6</sub>	C <sub>5</sub>	C <sub>4</sub>	C <sub>3</sub>	C <sub>2</sub>	E
C <sub>9</sub>	C <sub>10</sub>	C <sub>11</sub>	C <sub>12</sub>	C <sub>13</sub>	C <sub>14</sub>	C <sub>15</sub>	C <sub>1</sub>

Fig 1d

C <sub>9</sub>	C <sub>8</sub>	C <sub>7</sub>	C <sub>6</sub>	C <sub>5</sub>	C <sub>4</sub>	C <sub>3</sub>	C <sub>2</sub>
C <sub>10</sub>	C <sub>11</sub>	C <sub>12</sub>	C <sub>13</sub>	C <sub>14</sub>	C <sub>15</sub>	C <sub>1</sub>	E

Fig 1e




Fig 2




Fig 3

[illegible]




Fig 4



### Declaration and Power of Attorney Patent Application (Design or Utility)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: "Device for storage and conveyance of bulky holders".

the specification of which


- ☐ is attached hereto  
☒ was filed on January 23, 2002 as application serial no. 10/031,850  
and or PCT International Application number PCT/NL00/00518 and was amended  
on (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or 35 U.S.C. §365(b) of any foreign application(s) for patent or inventor's certificate, or 35 U.S.C. §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate of PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)		
Number 1012682	Country NL	Day/Month/Year Filed 23 July 1999
Number	Country	Day/Month/Year Filed
Number	Country	Day/Month/Year Filed



I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

Prior Provisional Application(s)	
Serial Number	Day/Month/Year Filing Date
Serial Number	Day/Month/Year Filing Date
Serial Number	Day/Month/Year Filing Date

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or under 35 U.S.C. §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

Prior U.S. or International Application(s)		
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. §1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

20030501 09:51:00



## Power of Attorney

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

### Attorney

### Registration Number

Charles R. Hoffmann	24,102
Ronald J. Baron	29,281
Gerald T. Bodner	30,449
A. Thomas Kammer	28,226
Irving N. Feit	28,601
Alan M. Sack	31,874
Algis Anilionis	36,995
Gregory W. Bachmann	41,593
Anthony E. Bennett	40,910
James F. Harrington	P-44,741
Glenn T. Henneberger	36,074
Richard LaCava	41,135
Kevin E. McDermott	35,946
Robert C. Morriss	42,910
Samir R. Patel	P-44,998
R. Glenn Schroeder	34,720
Susan A. Sipos	43,128
Roderick S.W. Turner	38,639
Steven T. Zuschlag	43,309

I hereby authorize them or others whom they may appoint to act and rely on instructions from and communicate directly with the person/organization who/which first sends this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instructed otherwise.

Please direct all correspondence in this case to at the address indicated below:

Ronald J. Baron  
Hoffman & Baron, L.L.P.  
6900 Jericho Turnpike  
Syosset, New York 11791  
United States of America

Full Name of Sole or First Inventor		
Family Name Hoogland	First Given Name Hendricus	Second Given Name Antonius
Residence and Citizenship		
City of Residence Krommenie	State or Country of Residence the Netherlands	Country of Citizenship the Netherlands
Post Office Address		
Street Address Ganimedesstraat 40	City Krommenie	State & Zip Code or Country 1562 ZN
Signature of Inventor		Date 15/2/2002